

# Smoke Detectors

Our Smoke Detectors communicate directly with our Emergency Response Centre.



## Features

Every home should be protected by a smoke detector. On detecting smoke, our smoke detectors will sound an audible alarm. They will then communicate with the INS LifeGuard Emergency Unit, which will transmit a signal to our Emergency Response Centre so appropriate action can be taken.

If the battery in the Smoke Detector runs low, the Detector will chirp intermittently for up to 30 days to alert the user.

## 240V Model Specifications

- 240 VAC operation with integrated non-user serviceable, rechargeable lithium battery back-up
- Requires installation by a qualified electrician
- Available in 304MHz or 433MHz depending on base unit - compatible with INS supplied equipment only.
- Alarm transmits wirelessly, no interlink required between detector and base unit
- Green LED on base indicates the detector has mains power connection.
- Red LED flashes at 45 second intervals to indicate detector is operational
- Alarm signal is via internal sounder (85 dBA), fast flashing LED, and the LifeGuard unit
- Dimensions: 113mm x 76mm  
Weight: 157 grams, Colour: off white

Both models are photoelectric type alarms, reset automatically on the detector, and have sensitivity factory set to suit Australian Standards. Designed and manufactured in Australia, they have a 2-year limited warranty (conditions apply).

For those who may be hearing-impaired, an optional strobe light can be linked with the 240V smoke detector which will flash to attract attention when the alarm goes off (see other side).

## Battery Operated Model Specifications

- Available in 304MHz or 433MHz depending on base unit - compatible with INS supplied equipment only.
- Alarm transmits wirelessly, no interlink required between detector and base unit
- Red LED flashes at 45 second intervals to indicate detector is operational
- Alarm signal is via internal sounder (85 dBA), fast flashing LED, and the LifeGuard unit
- Battery requires replacement once a year, unless depleted sooner
- Dimensions: 113mm x 76mm  
Weight: 157 grams, Colour: off white

*Specifications subject to change at discretion of INS LifeGuard.*



[www.theinsgroup.com.au](http://www.theinsgroup.com.au)

1 800 636 040

## Flashing Strobe Light (Optional)

---



### Features

---

For those who may be hearing impaired, this optional light can be linked with our 240V smoke detector and will flash to attract attention when the smoke alarm goes off.

Light has a 12-month limited warranty (conditions apply). Requires installation by a qualified electrician.

Designed and manufactured in Australia.

### Specifications

---

- Designed for connection to 240V mains
- Has a 9V battery back-up
- Must be interlinked to our 240V mains connection smoke detector
- Strobe light flashes when the smoke detector triggers an alarm
- Best installed in the room where the occupant spends the majority of their time.

*Specifications subject to change at discretion of INS LifeGuard.*